

品 種	ゲートバルブ《仕切弁》	ゲートバルブ《仕切弁》	チャッキバルブ《逆止弁》	スタンダードボア型(ロングネック) ボールバルブ
	5K JIS B2011	10K JIS B2011	10K JIS B2011	400型
				

製品記号	5BGN						10BGN						10BCN						BBHN						
	呼び径	L	H	D	W	箱入数	単価	L	H	D	W	箱入数	単価	L	H	D	W	箱入数	単価	L	H	D	W	箱入数	単価
15	1/2	50.0	126.0	55.0	0.4	42(7×6)	6,080	55.0	126.0	55.0	0.5	35(7×5)	8,660	65.0	43.0	—	0.4	48(12×4)	7,460	56.0	75.0	80.0	0.4	10	9,930
20	3/4	60.0	144.0	55.0	0.6	24(6×4)	8,120	65.0	149.0	70.0	0.7	24(6×4)	12,300	80.0	51.5	—	0.6	32(8×4)	9,410	65.0	79.0	80.0	0.5	8	12,800
25	1	65.0	171.0	80.0	0.9	12(6×2)	11,200	70.0	174.0	80.0	1.0	18(6×3)	17,100	90.0	58.5	—	0.8	16(8×2)	13,700	78.0	83.0	110.0	0.8	8	18,100
32	1 1/4	75.0	206.0	90.0	1.4	12(3×4)	19,100	80.0	215.0	90.0	1.4	12(3×4)	26,400	105.0	67.0	—	1.4	8(4×2)	23,800	86.0	98.0	110.0	1.0	6	26,400
40	1 1/2	85.0	235.0	100.0	1.8	8(2×4)	24,900	90.0	245.0	100.0	1.9	8(2×4)	36,800	120.0	73.5	—	1.9	8(4×2)	29,000	96.0	102.0	110.0	1.5	4	34,800
50	2	95.0	282.0	110.0	2.8	4(2×2)	36,700	100.0	288.0	110.0	2.9	4(2×2)	51,600	140.0	86.0	—	3.0	4(2×2)	46,800	109.0	109.0	140.0	2.3	4	50,400
本体材質	CAC911						CAC911						CAC911						CAC911						
弁体材質	CAC911						CAC911						CAC911						シートPTFE						
最高許容圧力	100℃以下の静流水…0.7MPa 100℃以下の脈動水…0.5MPa						100℃以下の静流水…1.4MPa 100℃以下の脈動水…1.0MPa						100℃以下の静流水…1.4MPa 100℃以下の脈動水…1.0MPa						85℃以下の静流水…1.4MPa 85℃以下の脈動水…1.0MPa						
備考																									

品 種	Y形ストレーナ	ゲートバルブ《仕切弁》	ゲートバルブ《仕切弁》	ストップバルブ《玉形弁》
	10K	5K JIS B2011	10K JIS B2011	10K JIS B2011
				

製品記号	10BYN						5BG						10BG						10BS						
	呼び径	L	H	D	W	箱入数	単価	L	H	D	W	箱入数	単価	L	H	D	W	箱入数	単価	L	H	D	W	箱入数	単価
15	1/2	91.0	51.0	—	0.4	8	6,990	50.0	126.0	55.0	0.4	42(7×6)	4,870	55.0	126.0	55.0	0.5	35(7×5)	6,950	65.0	93.0	55.0	0.5	36(6×6)	6,330
20	3/4	104.0	59.0	—	0.6	6	8,890	60.0	144.0	55.0	0.6	24(6×4)	6,530	65.0	149.0	70.0	0.7	24(6×4)	9,720	80.0	120.0	80.0	0.7	24(6×4)	8,500
25	1	123.0	72.0	—	0.9	6	13,000	65.0	171.0	80.0	0.9	12(6×2)	8,850	70.0	174.0	80.0	1.0	18(6×3)	13,800	90.0	131.0	90.0	1.0	16(4×4)	11,700
32	1 1/4	141.0	84.0	—	1.4	4	18,400	75.0	206.0	90.0	1.4	12(3×4)	15,000	80.0	215.0	90.0	1.4	12(3×4)	20,900	105.0	152.0	100.0	1.8	6(3×2)	22,200
40	1 1/2	160.0	100.0	—	2.1	4	22,400	85.0	235.0	100.0	1.9	8(2×4)	20,000	90.0	245.0	100.0	1.9	8(2×4)	29,200	120.0	167.0	110.0	2.0	8(2×4)	24,400
50	2	198.0	123.0	—	3.3	2	35,700	95.0	282.0	110.0	2.8	4(2×2)	29,200	100.0	288.0	110.0	3.0	4(2×2)	41,500	140.0	190.0	125.0	3.4	4(1×4)	39,500
65	2 1/2	—	—	—	—	—	—	—	—	—	—	—	—	120.0	376.0	125.0	8.6	1	82,000	—	—	—	—	—	—
本体材質	CAC911						CAC406						CAC406						CAC406						
弁体材質	スクリーンSUS304						CAC406						CAC406						CAC406						
最高許容圧力	85℃以下の静流水…1.4MPa 85℃以下の脈動水…1.0MPa						120℃以下の油、ガス、空気、脈動水…0.5MPa 飽和蒸気…0.2MPa 120℃以下の静流水…0.7MPa						120℃以下の油、ガス、空気、脈動水…1.0MPa 飽和蒸気…0.7MPa 120℃以下の静流水…1.4MPa						120℃以下の油、ガス、空気、脈動水…1.0MPa 飽和蒸気…1.0MPa 120℃以下の静流水…1.4MPa						
備考	●スクリーン：40メッシュ																								

品 種	チャッキバルブ《逆止弁》	Y形ストレーナ
	10K JIS B2011	10K
		

製品記号	10BC						10BY						
	呼び径	L	H	D	W	箱入数	単価	L	H	D	W	箱入数	単価
15	1/2	65.0	43.0	—	0.4	48(12×4)	5,960	80.0	49.0	—	0.4	48(8×6)	4,550
20	3/4	80.0	51.5	—	0.6	32(8×4)	7,550	100.0	57.0	—	0.6	36(6×6)	5,880
25	1	90.0	58.5	—	0.8	16(8×2)	10,900	115.0	70.0	—	0.8	24(6×4)	9,100
32	1 1/4	105.0	67.0	—	1.4	8(4×2)	19,100	135.0	82.0	—	1.2	16(4×4)	13,200
40	1 1/2	120.0	73.5	—	1.9	8(4×2)	23,100	160.0	98.0	—	1.8	8(4×2)	16,500
50	2	140.0	86.0	—	3.0	4(2×2)	37,600	195.0	121.0	—	3.0	4(2×2)	27,400
本体材質	CAC406						CAC						
弁体材質	CAC406						スクリーンSUS304						
最高許容圧力	120℃以下の油、ガス、空気、脈動水…1.0MPa 飽和蒸気…1.0MPa 120℃以下の静流水…1.4MPa						120℃以下の静流水…1.4MPa 飽和蒸気…お問合わせください						
備考	●スクリーン：60° 千鳥打抜きステンレス打抜板 ●スクリーン20~200メッシュも対応致します												