




製品記号	5BGN					10BGN					10BCN					BBHN									
	呼び径	L	H	D	W	箱入数	単価	L	H	D	W	箱入数	単価	L	H	D	W	箱入数	単価						
15	1/2	50.0	126.0	55.0	0.4	42(7×6)	4,800	55.0	126.0	55.0	0.5	35(7×5)	6,840	65.0	43.0	—	0.4	48(12×4)	5,890	56.0	75.0	80.0	0.4	10	7,510
20	3/4	60.0	144.0	55.0	0.6	24(6×4)	6,410	65.0	149.0	70.0	0.7	24(6×4)	9,640	80.0	52.0	—	0.6	32(8×4)	7,430	65.0	79.0	80.0	0.5	8	9,660
25	1	65.0	171.0	80.0	0.9	12(6×2)	8,750	70.0	174.0	80.0	1.0	18(6×3)	13,400	90.0	59.0	—	0.8	16(8×2)	10,700	78.0	83.0	110.0	0.8	8	13,600
32	1 1/4	75.0	206.0	90.0	1.4	12(3×4)	15,000	80.0	215.0	90.0	1.4	12(3×4)	20,800	105.0	67.0	—	1.4	8(4×2)	18,700	86.0	98.0	110.0	1.0	6	20,000
40	1 1/2	85.0	235.0	100.0	1.8	8(2×4)	19,600	90.0	245.0	100.0	1.9	8(2×4)	29,000	120.0	74.0	—	1.9	8(4×2)	22,800	96.0	102.0	110.0	1.5	4	26,300
50	2	95.0	282.0	110.0	2.8	4(2×2)	28,900	100.0	288.0	110.0	2.9	4(2×2)	40,700	140.0	8.0	—	3.0	4(2×2)	36,900	109.0	109.0	140.0	2.3	4	38,100
本体材質	CAC911					CAC911					CAC911					CAC911									
弁体材質	CAC911					CAC911					CAC911					シートPTFE									
最高許容圧力	100℃以下の静流水…0.7MPa 100℃以下の脈動水…0.5MPa					100℃以下の静流水…1.4MPa 100℃以下の脈動水…1.0MPa					100℃以下の静流水…1.4MPa 100℃以下の脈動水…1.0MPa					85℃以下の静流水…1.4MPa 85℃以下の脈動水…1.0MPa									
備考																									



製品記号	10BYN					5BG					10BG					10BS												
	呼び径	L	H	D	W	箱入数	単価	L	H	D	W	箱入数	単価	L	H	D	W	箱入数	単価	L	H	D	W	箱入数	単価			
15	1/2	91.0	51.0	—	0.4	8	5,520	50.0	126.0	55.0	0.4	42(7×6)	3,840	55.0	126.0	55.0	0.5	35(7×5)	5,480	65.0	92.0	55.0	0.5	36(6×6)	5,000			
20	3/4	104.0	59.0	—	0.6	6	7,020	60.0	144.0	55.0	0.6	24(6×4)	5,150	65.0	149.0	70.0	0.7	24(6×4)	7,670	80.0	120.0	80.0	0.7	24(6×4)	6,710			
25	1	123.0	72.0	—	0.9	6	10,200	65.0	171.0	80.0	0.9	12(6×2)	6,990	70.0	174.0	80.0	1.0	18(6×3)	10,800	90.0	132.0	90.0	1.0	16(4×4)	9,160			
32	1 1/4	141.0	84.0	—	1.4	4	14,500	75.0	206.0	90.0	1.4	12(3×4)	11,800	80.0	215.0	90.0	1.4	12(3×4)	16,500	105.0	152.0	100.0	1.8	6(3×2)	17,400			
40	1 1/2	160.0	100.0	—	2.1	4	17,600	85.0	235.0	100.0	1.9	8(2×4)	15,700	90.0	245.0	100.0	1.9	8(2×4)	23,000	120.0	165.0	110.0	2.0	8(2×4)	19,200			
50	2	198.0	123.0	—	3.3	2	28,100	95.0	282.0	110.0	2.8	4(2×2)	23,000	100.0	288.0	110.0	3.0	4(2×2)	32,700	140.0	191.0	125.0	3.4	4(1×4)	31,200			
65	2 1/2	—	—	—	—	—	—	—	—	—	—	—	—	120.0	376.0	155.0	8.6	1	64,700	—	—	—	—	—	—			
本体材質	CAC911					CAC406					CAC406					CAC406												
弁体材質	スクリーンSUS304					CAC406					CAC406					CAC406												
最高許容圧力	85℃以下の静流水…1.4MPa 85℃以下の脈動水…1.0MPa					120℃以下の油、ガス、空気、脈動水…0.5MPa 飽和蒸気…0.2MPa 120℃以下の静流水…0.7MPa					120℃以下の油、ガス、空気、脈動水…1.0MPa 飽和蒸気…0.7MPa 120℃以下の静流水…1.4MPa					120℃以下の油、ガス、空気、脈動水…1.0MPa 飽和蒸気…1.0MPa 120℃以下の静流水…1.4MPa												
備考	●スクリーン：40メッシュ																											



製品記号	10BC					10BY							
	呼び径	L	H	D	W	箱入数	単価	L	H	D	W	箱入数	単価
15	1/2	65.0	43.0	—	0.4	48(12×4)	4,700	80.0	49.0	—	0.4	48(8×6)	3,590
20	3/4	80.0	52.0	—	0.6	32(8×4)	5,960	100.0	57.0	—	0.6	36(6×6)	4,640
25	1	90.0	59.0	—	0.8	16(8×2)	8,560	115.0	70.0	—	0.8	24(6×4)	7,190
32	1 1/4	105.0	67.0	—	1.4	8(4×2)	15,000	135.0	82.0	—	1.2	16(4×4)	10,400
40	1 1/2	120.0	74.0	—	1.9	8(4×2)	18,200	160.0	98.0	—	1.8	8(4×2)	13,000
50	2	140.0	86.0	—	3.0	4(2×2)	29,600	195.0	121.0	—	3.0	4(2×2)	21,600
本体材質	CAC406					CAC							
弁体材質	CAC406					スクリーンSUS304							
最高許容圧力	120℃以下の油、ガス、空気、脈動水…1.0MPa 飽和蒸気…1.0MPa 120℃以下の静流水…1.4MPa					120℃以下の静流水…1.4MPa 飽和蒸気…お問合わせください							
備考	●スクリーン：60° 千鳥打抜きステンレス打抜板 ●スクリーン20~200メッシュも対応致します												